




TEST REPORT


Applicant: ZHEJIANG HECHUAN TECHNOLOGY CO., LTD
Address of Applicant: No. 9, Fucai Road, Longyou Industrial Zone, Quzhou City,
Zhejiang Province, P.R. China

Equipment Under Test (EUT)

Product Name: SERVO MOTOR
Model No.: Please refer to page 5.
Brand Name: 
Applicable standards: EN 60034-1:2010+AC:2010
Date of sample receipt: August 26, 2019
Date of Test: August 26, 2019 To September 6, 2019
Date of report issued: September 6, 2019
Test Result : PASS

The CE mark as shown below can be used, under the responsibility of the manufacturer, after completion of an EU Declaration of Conformity and compliance with all relevant EU Directives.

Authorized Signature



Kevin Wang
Laboratory Manager





TEST REPORT

EN 60034-1

Rotating electrical machines - Part 1: Rating and performance

Report reference No......: EBO1908102-E163
Testing Laboratory Name: Shenzhen EBO Testing Center
Address: 3/F, Building A, Qinye Business Center, Xin'an Sixth Road, 82th District, Bao'an, Shenzhen, China
Tested by (name + signature).....: Bernie Xia *Bernie Xia*
Approved by (name + signature).....: Kevin Wang *Kevin Wang*
Date of issue: September 6, 2019
Total number of pages: 47 pages



Test specification:
Standard.....: EN 60034-1:2010+AC:2010
Test procedure: LVD
Non-standard test method: N/A

Applicant's name.....: ZHEJIANG HECHUAN TECHNOLOGY CO., LTD
Address: No. 9, Fucai Road, Longyou Industrial Zone, Quzhou City, Zhejiang Province, P.R. China
Manufacturer.....: ZHEJIANG HECHUAN TECHNOLOGY CO., LTD
Address: No. 9, Fucai Road, Longyou Industrial Zone, Quzhou City, Zhejiang Province, P.R. China

Test item description: SERVO MOTOR
Brand Name.....: 
Model/Type reference: Please refer to page 5
Test Model No.:: SV-X3MH075A-N2LN
Ratings: Input :AC 220-240V, 1.1-10.4A, 0.2-2.3KW, 50/60Hz
 Output : AC 0-220V, 0.6-12.2A, 50W-2KW



Test item particulars	
Classification of installation and use	Mobile apparatus
Supply Connection	AC Mains Operated
Possible test case verdicts:	
- test case does not apply to the test object.....	N (Not Applicable)
- test object does meet the requirement	P (Pass)
- test object does not meet the requirement	F (Fail)
Testing.....	
Date of receipt of test item.....	August 26, 2019
Date (s) of performance of tests.....	August 26, 2019 To September 6, 2019
General remarks:	
<p>The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory. "(see Enclosure #)" refers to additional information appended to the report. "(see appended table)" refers to a table appended to the report.</p> <p>Throughout this report a point is used as the decimal separator.</p> <p>This document is issued by the company under its General Conditions of Service accessible at www.ebotest.com. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.</p> <p>Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.</p> <p>Unless otherwise stated: (a) the results shown in this document refer only to the sample(s) tested and (b) such sample(s) are retained for 1 month. This document cannot be reproduced except in full, without prior approval of the company.</p>	
General product information:	
SERVO MOTOR, Power by AC mains, For indoor use only.	
Instructions and equipment marking related to safety is applied in the language that is acceptable in the country in which the equipment is to be sold.	

Tests performed (name of test and test clause):

The sample(s) tested complies with the requirements of EN 60034-1
When determining the test conclusion, the Measurement Uncertainty of test has been considered.

Summary of compliance with National Differences

Compliance with the National requirements of CENELEC common modification.

Copy of marking plates:

Product Name: SERVO MOTOR
Model no.: SV-X3MH075A-N2LN
Input :AC 220-240V, 1.1-10.4A, 0.2-2.3KW, 50/60Hz
Output : AC 0-220V, 0.6-12.2A, 50W-2KW



ZHEJIANG HECHUAN TECHNOLOGY CO., LTD
No. 9, Fucai Road, Longyou Industrial Zone, Quzhou
City, Zhejiang Province, P.R. China City, Zhejiang
Province, P.R. China



Model No.:

SV-X3MM005A-N2LN	SV-X3MA100A-N2LA	SV-X1MM005A-N2LN	SV-X1MA100A-N2LA
SV-X3MM005A-N2LA	SV-X3MA100A-B2LN	SV-X1MM005A-N2LA	SV-X1MA100A-B2LN
SV-X3MM005A-B2LN	SV-X3MA100A-B2LA	SV-X1MM005A-B2LN	SV-X1MA100A-B2LA
SV-X3MM005A-B2LA	SV-X3MM100A-N2LN	SV-X1MM005A-B2LA	SV-X1MM100A-N2LN
SV-X3MM010A-N2LN	SV-X3MM100A-N2LA	SV-X1MM010A-N2LN	SV-X1MM100A-N2LA
SV-X3MM010A-N2LA	SV-X3MM100A-B2LN	SV-X1MM010A-N2LA	SV-X1MM100A-B2LN
SV-X3MM010A-B2LN	SV-X3MM100A-B2LA	SV-X1MM010A-B2LN	SV-X1MM100A-B2LA
SV-X3MM010A-B2LA	SV-X3MH100A-N2LN	SV-X1MM010A-B2LA	SV-X1MH100A-N2LN
SV-X3MM020A-N2LN	SV-X3MH100A-N2LA	SV-X1MM020A-N2LN	SV-X1MH100A-N2LA
SV-X3MM020A-N2LA	SV-X3MH100A-B2LN	SV-X1MM020A-N2LA	SV-X1MH100A-B2LN
SV-X3MM020A-B2LN	SV-X3MH100A-B2LA	SV-X1MM020A-B2LN	SV-X1MH100A-B2LA
SV-X3MM020A-B2LA	SV-X3MA150A-N2LN	SV-X1MM020A-B2LA	SV-X1MA150A-N2LN
SV-X3MH020A-N2LN	SV-X3MA150A-N2LA	SV-X1MH020A-N2LN	SV-X1MA150A-N2LA
SV-X3MH020A-N2LA	SV-X3MA150A-B2LN	SV-X1MH020A-N2LA	SV-X1MA150A-B2LN
SV-X3MH020A-B2LN	SV-X3MA150A-B2LA	SV-X1MH020A-B2LN	SV-X1MA150A-B2LA
SV-X3MH020A-B2LA	SV-X3MM150A-N2LN	SV-X1MH020A-B2LA	SV-X1MM150A-N2LN
SV-X3MM040A-N2LN	SV-X3MM150A-N2LA	SV-X1MM040A-N2LN	SV-X1MM150A-N2LA
SV-X3MM040A-N2LA	SV-X3MM150A-B2LN	SV-X1MM040A-N2LA	SV-X1MM150A-B2LN
SV-X3MM040A-B2LN	SV-X3MM150A-B2LA	SV-X1MM040A-B2LN	SV-X1MM150A-B2LA
SV-X3MM040A-B2LA	SV-X3MH150A-N2LN	SV-X1MM040A-B2LA	SV-X1MH150A-N2LN
SV-X3MH040A-N2LN	SV-X3MH150A-N2LA	SV-X1MH040A-N2LN	SV-X1MH150A-N2LA
SV-X3MH040A-N2LA	SV-X3MH150A-B2LN	SV-X1MH040A-N2LA	SV-X1MH150A-B2LN
SV-X3MH040A-B2LN	SV-X3MH150A-B2LA	SV-X1MH040A-B2LN	SV-X1MH150A-B2LA
SV-X3MH040A-B2LA	SV-X3MA200A-N2LN	SV-X1MH040A-B2LA	SV-X1MA200A-N2LN
SV-X3MM075A-N2LN	SV-X3MA200A-N2LA	SV-X1MM075A-N2LN	SV-X1MA200A-N2LA
SV-X3MM075A-N2LA	SV-X3MA200A-B2LN	SV-X1MM075A-N2LA	SV-X1MA200A-B2LN
SV-X3MM075A-B2LN	SV-X3MA200A-B2LA	SV-X1MM075A-B2LN	SV-X1MA200A-B2LA
SV-X3MM075A-B2LA	SV-X3MM200A-N2LN	SV-X1MM075A-B2LA	SV-X1MM200A-N2LN
SV-X3MH075A-N2LN	SV-X3MM200A-N2LA	SV-X1MH075A-N2LN	SV-X1MM200A-N2LA
SV-X3MH075A-N2LA	SV-X3MM200A-B2LN	SV-X1MH075A-N2LA	SV-X1MM200A-B2LN
SV-X3MH075A-B2LN	SV-X3MM200A-B2LA	SV-X1MH075A-B2LN	SV-X1MM200A-B2LA
SV-X3MH075A-B2LA	SV-X3MH200A-N2LN	SV-X1MH075A-B2LA	SV-X1MH200A-N2LN
SV-X3MA100A-N2LN	SV-X3MH200A-N2LA	SV-X1MA100A-N2LN	SV-X1MH200A-N2LA
	SV-X3MH200A-B2LN		SV-X1MH200A-B2LN
	SV-X3MH200A-B2LA		SV-X1MH200A-B2LA

Remark: All models are identical in the same PCB layout, interior structure and electrical circuits. The only differences are the model name and appearance color for commercial purpose.



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
4	Duty		P
4.1	Declaration of duty		P
	It is the responsibility of the purchaser to declare the duty. The purchaser may describe the duty by one of the following:	Duty type S1	P
	The purchaser normally cannot provide values for the moment of inertia of the motor (JM) or the relative thermal life expectancy (TL), see Annex A. These values are provided by the manufacturer.		N
	Where the purchaser does not declare a duty, the manufacturer shall assume that duty type S1 (continuous running duty) applies.		P
4.2	Duty types		P
4.2.1	Duty type S1 – Continuous running duty		P
4.2.2	Duty type S2 – Short-time duty		N
4.2.3	Duty type S3 – Intermittent periodic duty 2		N
4.2.4	Duty type S4 – Intermittent periodic duty with starting 2		N
4.2.5	Duty type S5 – Intermittent periodic duty with electric braking 2		N
4.2.6	Duty type S6 – Continuous-operation periodic duty 2		N
4.2.7	Duty type S7 – Continuous-operation periodic duty with electric braking 2		N
4.2.8	Duty type S8 – Continuous-operation periodic duty with related load/speed changes 2		N
4.2.9	Duty type S9 – Duty with non-periodic load and speed variations		N
4.2.10	Duty type S10 – Duty with discrete constant loads and speeds		N
5	Rating		P
5.1	Assignment of rating		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	The rating, as defined in 3.2, shall be assigned by the manufacturer. In assigning the rating the manufacturer shall select one of the classes of rating defined in 5.2.1 to 5.2.6. The designation of the class of rating shall be written after the rated output. If no designation is stated, rating for continuous running duty applies.		P
	When accessory components (such as reactors, capacitors, etc.) are connected by the manufacturer as part of the machine, the rated values shall refer to the supply terminals of the whole arrangement	No such accessory components provided	N
	Special considerations are required when assigning ratings to machines fed from or supplying static converters. IEC 60034-17 gives guidance for the case of cage induction motors covered in IEC 60034-12.		N
5.2	Classes of rating		P
5.2.1	Rating for continuous running duty		P
	A rating at which the machine may be operated for an unlimited period, while complying with the requirements of this standard.		P
	This class of rating corresponds to duty type S1 and is designated as for the duty type S1.		P
5.2.2	Rating for short-time duty		N
	A rating at which the machine may be operated for a limited period, starting at ambient temperature, while complying with the requirements of this standard.		N
	This class of rating corresponds to duty type S2 and is designated as for the duty type S2.		N
5.2.3	Rating for periodic duty		N
	A rating at which the machine may be operated on duty cycles, while complying with the requirements of this standard.		N
	This class of rating corresponds to one of the periodic duty types S3 to S8 and is designated as for the corresponding duty type.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	Unless otherwise specified, the duration of a duty cycle shall be 10 min and the cyclic duration factor shall be one of the following values:		N
5.2.4	Rating for non-periodic duty		N
	A rating at which the machine may be operated non-periodically while complying with the requirements of this standard.		N
	This class of rating corresponds to the non-periodic duty type S9 and is designated as for the duty type S9.		N
5.2.5	Rating for duty with discrete constant loads and speeds		N
	A rating at which the machine may be operated with the associated loads and speeds of duty type S10 for an unlimited period of time while complying with the requirements of this standard. The maximum permissible load within one cycle shall take into consideration all parts of the machine, for example, the insulation system regarding the validity of the exponential law for the relative thermal life expectancy, bearings with respect to temperature, other parts with respect to thermal expansion. Unless specified in other relevant IEC standards, the maximum load shall not exceed 1,15 times the value of the load based on duty type S1. The minimum load may have the value zero, the machine operating at no-load or being de-energized and at rest. Considerations for the application of this class of rating are		N
	This class of rating corresponds to the duty type S10 and is designated as for the duty type S10.		N
5.2.6	Rating for equivalent loading		N
	A rating, for test purposes, at which the machine may be operated at constant load until thermal equilibrium is reached and which results in the same stator winding temperature rise as the average temperature rise during one load cycle of the specified duty type.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	This class of rating, if applied, is designated 'equ'.		N
5.3	Selection of a class of rating		P
	A machine manufactured for general purpose shall have a rating for continuous running duty and be capable of performing duty type S1.		P
	If the duty has not been specified by the purchaser, duty type S1 applies and the rating assigned shall be a rating for continuous running duty.		P
	When a machine is intended to have a rating for short-time duty, the rating shall be based on duty type S2, see 4.2.2.		N
	When a machine is intended to supply varying loads or loads including a time of no-load or times where the machine will be in a state of de-energized and at rest, the rating shall be a rating for periodic duty based on a duty type selected from duty types S3 to S8, see 4.2.3 to 4.2.8.		N
	When a machine is intended non-periodically to supply variable loads at variable speeds, including overloads, the rating shall be a rating for non-periodic duty based on duty type S9, see 4.2.9.		N
	When a machine is intended to supply discrete constant loads including times of overload or times of no-load (or de-energized and at rest) the rating shall be a rating with discrete constant loads based on duty type S10, see 4.2.10.		N
5.4	Allocation of outputs to class of rating		P
	In the determination of the rating		P
	For duty types S1 to S8, the specified value(s) of the constant load(s) shall be the rated output(s), see 4.2.1 to 4.2.8		P
	For duty types S9 and S10, the reference value of the load based on duty type S1 shall be taken as the rated output, see 4.2.9 and 4.2.10.		N
5.5	Rated output		P
5.5.1	DC generators	Motor	N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	The rated output is the output at the terminals and shall be expressed in watts (W).		N
5.5.2	AC generators		N
	The rated output is the apparent power at the terminals and shall be expressed in voltamperes (VA) together with the power factor.		N
	The rated power factor for synchronous generators shall be 0,8 lagging (over-excited), unless otherwise specified by the purchaser.		N
5.5.3	Motors		P
	The rated output is the mechanical power available at the shaft and shall be expressed in watts (W).		P
5.5.4	Synchronous condensers	No such condensers used	N
	The rated output is the reactive power at the terminals and shall be expressed in volt-amperes reactive (var) in leading (under-excited) and lagging (over-excited) conditions.		N
5.6	Rated voltage		P
5.6.1	DC generators		N
	For d.c. generators intended to operate over a relatively small range of voltage, the rated output and current shall apply at the highest voltage of the range, unless otherwise specified, see also 7.3.		N
5.6.2	AC generators		N
	For a.c. generators intended to operate over a relatively small range of voltage, the rated output and power factor shall apply at any voltage within the range, unless otherwise specified, see also 7.3.		N
5.7	Co-ordination of voltages and outputs		N
	It is not practical to build machines of all ratings for all rated voltages. In general, for a.c.machines, based on design and manufacturing considerations, preferred voltage ratings above 1 kV in terms of rated output are as shown in Table 1.		N
5.8	Machines with more than one rating	Only single rating provided	N
	For machines with more than one rating, the machine shall comply with this standard in all respects at each rating.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict

	For multi-speed motors, a rating shall be assigned for each speed.		N
	When a rated quantity (output, voltage, speed, etc.) may assume several values or vary continuously within two limits, the rating shall be stated at these values or limits. This provision does not apply to voltage and frequency variations during operation as defined in 7.3 or to star-delta connections intended for starting.		N

6	Site operating conditions		P
6.1	General		P
	Unless otherwise specified, machines shall be suitable for the following site operation conditions. For site operating conditions deviating from those values, corrections are given in Clause 8.		P
6.2	Altitude		P
	The altitude shall not exceed 1 000 m above sea-level.		P
6.3	Maximum ambient air temperature		P
	The ambient air temperature shall not exceed 40 °C.	Ambient not exceed 40 °C.	P
6.4	Minimum ambient air temperature		P
	The ambient air temperature shall not be less than -15 °C for any machine.	Ambient not exceed -15 °C.	P
	The ambient air temperature shall be not less than 0 °C for a machine		N

6.5	Water coolant temperature	Air temperature	N
	The water coolant temperature at the inlet to a machine or heat exchanger, or the ambient water (in the case of submersible machines with surface cooling or machines with water jacket cooling) shall not exceed +25 °C nor be less than +5 °C.		N
6.6	Storage and transport		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	When temperatures lower than specified in 6.4 are expected during transportation, storage, or after installation, the purchaser shall inform the manufacturer and specify the expected minimum temperature.		P
6.7	Purity of hydrogen coolant		N
	Hydrogen cooled machines shall be capable of operating at rated output under rated conditions with a coolant containing not less than 95 % hydrogen by volume.		N
	For calculating efficiency in accordance with IEC 60034-2, the standard composition of the gaseous mixture shall be 98 % hydrogen and 2 % air by volume, at the specified values of pressure and temperature of the re-cooled gas, unless otherwise agreed. Windage losses shall be calculated at the corresponding density.		N
7	Electrical operating conditions		P
7.1	Electrical supply		P
	For three-phase a.c. machines, 50 Hz or 60 Hz, intended to be directly connected to distribution or utilisation systems, the rated voltages shall be derived from the nominal voltages given in IEC 60038.		N
	For a.c. motors supplied from static converters these restrictions on voltage, frequency and waveform do not apply. In this case, the rated voltages shall be selected by agreement.		P
7.2	Form and symmetry of voltages and currents		P
7.2.1	AC motors		P
7.2.1.1	AC motors rated for use on a power supply of fixed frequency, supplied from an a.c. generator (whether local or via a supply network) shall be suitable for operation on a supply voltage having a harmonic voltage factor (HVF) not exceeding:		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	0,02 for single-phase motors and three-phase motors, including synchronous motors but excluding motors of design N (see IEC 60034-12), unless the manufacturer declares otherwise.		P
	0,03 for design N motors.		N
	Three-phase a.c. motors shall be suitable for operation on a three-phase voltage system having a negative-sequence component not exceeding 1 % of the positive-sequence component over a long period, or 1,5 % for a short period not exceeding a few minutes, and a zero-sequence component not exceeding 1 % of the positive-sequence component.		N
	Should the limiting values of the HVF and of the negative-sequence and zero-sequence components occur simultaneously in service at the rated load, this shall not lead to any harmful temperature in the motor and it is recommended that the resulting excess temperature rise related to the limits specified in this standard should be not more than approximately 10 K.		N
7.2.1.2	AC motors supplied from static converters have to tolerate higher harmonic contents of the supply voltage, see IEC 60034-17 for the case of cage motors within the scope of IEC 60034-12.		P
7.2.2	AC generators		N
	Three-phase a.c. generators shall be suitable for supplying circuits which, when supplied by a system of balanced and sinusoidal voltages:		N
	Should the limits of deformation and imbalance occur simultaneously in service at the rated load, this shall not lead to any harmful temperature in the generator and it is recommended that the resulting excess temperature rise related to the limits specified in this standard should be not more than approximately 10 K.		N
7.2.3	Synchronous machines	Asynchronous machines	N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	Unless otherwise specified, three-phase synchronous machines shall be capable of operating continuously on an unbalanced system in such a way that, with none of the phase currents exceeding the rated current, the ratio of the negative-sequence component of current (I_2) to the rated current (I_N) does not exceed the values in Table 2 and under fault conditions shall be capable of operation with the product of $(I_2/I_N)^2$ and time (t) not exceeding the values in Table 2.		N
7.2.4	DC motors supplied from static power converters		N
	In the case of a d.c. motor supplied from a static power converter, the pulsating voltage and current affect the performance of the machine. Losses and temperature rise will increase and the commutation is more difficult compared with a d.c. motor supplied from a pure d.c. power source.		N
	It is necessary, therefore, for motors with a rated output exceeding 5 kW, intended for supply from a static power converter, to be designed for operation from a specified supply, and, if considered necessary by the motor manufacturer, for an external inductance to be provided for reducing the undulation.		N
	The static power converter supply shall be characterized by means of an identification code, as follows:		N
	Motors with rated output not exceeding 5 kW, instead of being tied to a specific type of static power converter, may be designed for use with any static power converter, with or without external inductance, provided that the rated form factor for which the motor is designed will not be surpassed and that the insulation level of the motor armature circuit is appropriate for the rated alternating voltage at the input terminals of the static power converter.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	In all cases, the undulation of the static power converter output current is assumed to be so low as to result in a current ripple factor not higher than 0,1 at rated conditions.		N
7.3	Voltage and frequency variations during operation		P
	For a.c. machines rated for use on a power supply of fixed frequency supplied from an a.c. generator (whether local or via a supply network), combinations of voltage variation and frequency variation are classified as being either zone A or zone B, in accordance with Figure 11 for generators and synchronous condensers, and Figure 12 for motors.		P
	For d.c. machines, when directly connected to a normally constant d.c. bus, zones A and B apply only to the voltages.		N
	A machine shall be capable of performing its primary function, as specified in Table 3, continuously within zone A, but need not comply fully with its performance at rated voltage and frequency (see rating point in Figures 11 and 12), and may exhibit some deviations. Temperature rises may be higher than at rated voltage and frequency.		P
	A machine shall be capable of performing its primary function within zone B, but may exhibit greater deviations from its performance at rated voltage and frequency than in zone A. Temperature rises may be higher than at rated voltage and frequency and most likely will be higher than those in zone A. Extended operation at the perimeter of zone B is not recommended.		N
7.4	Three-phase a.c. machines operating on unearthed systems		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	Three-phase a.c. machines shall be suitable for continuous operation with the neutral at or near earth potential. They shall also be suitable for operation on unearthed systems with one line at earth potential for infrequent periods of short duration, for example as required for normal fault clearance. If it is intended to run the machine continuously or for prolonged periods in this condition, a machine with a level of insulation suitable for this condition will be required.		N
	If the winding does not have the same insulation at the line and neutral ends, this shall be stated by the manufacturer.		N
7.5	Voltage (peak and gradient) withstand levels		N
	For a.c. motors the manufacturer shall declare a limiting value for the peak voltage and for the voltage gradient in continuous operation.		N
	For cage induction motors within the scope of IEC 60034-12, see also IEC 60034-17.		N
	For high-voltage a.c. motors, see also IEC 60034-15.		N
8	Thermal performance and tests		P
8.1	Thermal class	According to IEC60034-18	P
	A thermal class in accordance with IEC 62114 shall be assigned to the insulation systems used in machines.		P
	It is the responsibility of the manufacturer of the machine to interpret the results obtained by thermal endurance testing according to the appropriate part of IEC 60034-18.		P
8.2	Reference coolant		N
	The reference coolant for a given method of cooling the machine is specified in Table 4.		N
	If a third coolant is used, temperature rise shall be measured above the temperature of the primary or secondary coolant as specified in Table 4.		N
8.3	Conditions for thermal tests		P
8.3.1	Electrical supply		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	During thermal testing of an a.c. motor the HVF of the supply shall not exceed 0,015 and the negative-sequence component of the system of voltages shall be less than 0,5 % of the positive-sequence component, the influence of the zero-sequence component being eliminated.		P
	By agreement, the negative-sequence component of the system of currents may be measured instead of the negative-sequence component of the system of voltages. The negativesequene component of the system of currents shall not exceed 2,5 % of the positivesequene component.		N
8.3.2	Temperature of machine before test		P
	If the temperature of a winding is to be determined from the increase of resistance, the initial winding temperature shall not differ from the coolant by more than 2 K.		N
	When a machine is to be tested on a short-time rating (duty type S2) its temperature at the beginning of the thermal test shall be within 5 K of the temperature of the coolant.		P
8.3.3	Temperature of coolant		N
	A machine may be tested at any convenient value of coolant temperature. See Table 11 (for indirect cooled windings) or Table 14 (for direct cooled windings).		N
8.3.4	Measurement of coolant temperature during test		N
	The value to be adopted for the temperature of a coolant during a test shall be the mean of the readings of the temperature detectors taken at equal intervals of time during the last quarter of the duration of the test. To reduce errors due to the time lag of the change of temperature of large machines following variations in the temperature of the coolant, all reasonable precautions shall be taken to minimize such variations.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
8.3.4.1	Open machines or closed machines without heat exchangers (cooled by surrounding ambient air or gas)		N
	The temperature of the ambient air or gas shall be measured by means of several detectors placed at different points around and halfway up the machine at 1 m to 2 m from it. Each detector shall be protected from radiant heat and draughts.		N
8.3.4.2	Machines cooled by air or gas from a remote source through ventilation ducts and machines with separately mounted heat exchangers		N
	The temperature of the primary coolant shall be measured where it enters the machine.		
8.3.4.3	Closed machines with machine-mounted or internal heat exchangers		N
	The temperature of the primary coolant shall be measured where it enters the machine. The temperature of the secondary coolant shall be measured where it enters the heat exchanger.		N
8.4	Temperature rise of a part of a machine		P
	The temperature rise, $\Delta\theta$, of a part of a machine is the difference between the temperature of that part measured by the appropriate method in accordance with 8.5, and the temperature of the coolant measured in accordance with 8.3.4.		P
	For comparison with the limits of temperature rise (see Table 7 or 8) or of temperature (see Table 12), when possible, the temperature shall be measured immediately before the machine is shut down at the end of the thermal test, as described in 8.7.		N
	When this is not possible, for example, when using the direct measurement of resistance method, see 8.6.2.3.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	For machines tested on actual periodic duty (duty types S3 to S8) the temperature at the end of the test shall be taken as that at the middle of the period causing the greatest heating in the last cycle of operation (but see also 8.7.3).		N
8.5	Methods of measurement of temperature		P
8.5.1	General		P
	Three methods of measuring the temperature of windings and other parts are recognized:		N
	Different methods shall not be used as a check upon one another.		N
	For indirect testing see IEC 61986.		P
8.5.2	Resistance method		P
	The temperature of the windings is determined from the increase of the resistance of the windings.	See append table	P
8.5.3	Embedded temperature detector (ETD) method	Resistance method	N
	The temperature is determined by means of temperature detectors (e.g. resistance thermometers, thermocouples or semi-conductor negative coefficient detectors) built into the machine during construction, at points which are inaccessible after the machine is completed.		N
8.5.4	Thermometer method		N
	The temperature is determined by thermometers applied to accessible surfaces of the completed machine. The term 'thermometer' includes not only bulb-thermometers, but also non-embedded thermocouples and resistance thermometers. When bulb-thermometers are used in places where there is a strong varying or moving magnetic field, alcohol thermometers shall be used in preference to mercury thermometers.		N
8.6	Determination of winding temperature		P
8.6.1	Choice of method		P
	In general, for measuring the temperature of the windings of a machine, the resistance method in accordance with 8.5.1 shall be applied (but see also 8.6.2.3.3).		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	For a.c. stator windings of machines having a rated output of 5 000 kW (or kVA) or more the ETD method shall be used.		N
	For a.c. machines having a rated output less than 5 000 kW (or kVA) but greater than 200 kW (or kVA) the manufacturer shall choose either the resistance or the ETD method, unless otherwise agreed.		N
	For a.c. machines having a rated output less than or equal to 200 kW (or kVA) the manufacturer shall choose the direct measurement version or the superposition version of the resistance method (see 8.6.2.1), unless otherwise agreed (but see also below).		N
	For machines having a rated output less than or equal to 600 W (or VA), when the windings are non-uniform or severe complications are involved in making the necessary connections, the temperature may be determined by means of thermometers. Temperature rise limits in accordance with Table 7, item 1d for resistance method shall apply.		N
	The thermometer method is recognized in the following cases:		N
	For a.c. stator windings having only one coil-side per slot, the ETD method shall not be used for verifying compliance with this standard: the resistance method shall be used.		N
	For other windings having one coil-side per slot and for end windings the ETD method shall not be used for verifying compliance with this standard.		N
	For windings of armatures having commutators and for field windings the resistance method and the thermometer method are recognized. The resistance method is preferred for stationary field windings of d.c. machines having more one layer the ETD method may be used.		N
8.6.2	Determination by resistance method		P
8.6.2.1	Measurement		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	One of the following methods shall be used:		P
8.6.2.2	Calculation	The value see append table	P
8.6.2.3	Correction for stopping time		N
8.6.2.3.1	General		N
	The measurement of temperatures at the end of the thermal test by the direct measurement resistance method requires a quick shutdown. A carefully planned procedure and an adequate number of people are required.		N
8.6.2.3.2	Short stopping time		N
	If the initial resistance reading is obtained within the time interval specified in Table 5, that reading shall be accepted for the temperature measurement.		N
8.6.2.3.3	Extended stopping time		N
	If a resistance reading cannot be made in the time interval specified in Table 5, it shall be made as soon as possible but not after more than twice the interval specified in Table 5, and additional readings shall be taken at intervals of approximately 1 min until these readings have begun a distinct decline from their maximum value. A curve of these readings shall be plotted as a function of time and extrapolated to the appropriate time interval of Table 5 for the rated output of the machine. A semi-logarithmic plot is recommended where temperature is plotted on the logarithmic scale. The value of temperature thus obtained shall be considered as the temperature at shutdown. If successive measurements show increasing temperatures after shutdown the highest value shall be taken.		N
	If a resistance reading cannot be made until after twice the time interval specified in Table 5, this method of correction shall only be used by agreement		N
8.6.2.3.4	Windings with one coil-side per slot		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	For machines with one coil-side per slot, the resistance method by direct measurement may be used if the machine comes to rest within the time interval specified in Table 5. If the machine takes more than 90 s to come to rest after switching off the power, the superposition method may be used if previously agreed.		N
8.6.3	Determination by ETD method		N
8.6.3.1	General		N
	The detectors shall be suitably distributed throughout the winding and the number of detectors installed shall be not less than six.		N
	All reasonable efforts, consistent with safety, shall be made to place the detectors at the points where the highest temperatures are likely to occur, in such a manner that they are effectively protected against contact with the primary coolant.		N
	The highest reading from the ETD elements shall be used to determine the temperature of the winding.		N
8.6.3.2	Two or more coil-sides per slot		N
	The detectors shall be located between the insulated coil-sides within the slot in positions at which the highest temperatures are likely to occur.		N
8.6.3.3	One coil-side per slot		N
	The detectors shall be located between the wedge and the outside of the winding insulation in positions at which the highest temperatures are likely to occur, but see also 8.6.1.		N
8.6.3.4	End windings		N
	The temperature detectors shall be located between two adjacent coil-sides within the end windings in positions where the highest temperatures are likely to occur. The sensing point of each detector shall be in close contact with the surface of a coil-side and be adequately protected against the influence of the coolant, but see also 8.6.1.		N
8.6.4	Determination by thermometer method	Resistance method	N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	All reasonable efforts, consistent with safety, shall be made to place thermometers at the point, or points where the highest temperatures are likely to occur (e.g. in the end windings close to the core iron) in such a manner that they are effectively protected against contact with the primary coolant and are in good thermal contact with the winding or other part of the machine.		N
	The highest reading from any thermometer shall be taken to be the temperature of the winding or other part of the machine.		N
8.7	Duration of thermal tests		P
8.7.1	Rating for continuous running duty		P
	The test shall be continued until thermal equilibrium has been reached.		P
8.7.2	Rating for short-time duty		N
	The duration of the test shall be the time given in the rating.		N
8.7.3	Rating for periodic duty		N
	Normally the rating for equivalent loading assigned by the manufacturer (see 5.2.6) shall be applied until thermal equilibrium has been reached. If a test on the actual duty is agreed, the load cycle specified shall be applied and continued until practically identical temperature cycles are obtained. The criterion for this shall be that a straight line between the corresponding points of successive duty cycles on a temperature plot has a gradient of less than 2 K per hour. If necessary, measurements shall be taken at reasonable intervals over a period of time.		N
8.7.4	Ratings for non-periodic duty and for duty with discrete constant loads		N
	The rating for equivalent loading assigned by the manufacturer (see 5.2.6) shall be applied until thermal equilibrium has been reached.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
8.8	Determination of the thermal equivalent time constant for machines of duty type S9		N
	The thermal equivalent time constant with ventilation as in normal operating conditions, suitable for approximate determination of the temperature course, can be determined from the cooling curve plotted in the same manner as in 8.6.2.3. The value of the time constant is 1,44 times (that is to say, $1/\ln(2)$ times) the time taken by the machine to cool to one-half of the full load temperature rise, after its disconnection from the supply.		N
8.9	Measurement of bearing temperature		N
	Either the thermometer method or the ETD method may be used.		N
	The measuring point shall be as near as possible to one of the two locations specified in Table 6.		N
	The thermal resistance between the temperature detector and the object whose temperature is to be measured shall be minimized; for example, air gaps shall be packed with thermally conducting paste.		N
8.10	Limits of temperature and of temperature rise		P
	Limits are given for operation under site operating conditions specified in Clause 6 and at rating for continuous running duty (reference conditions), followed by rules for the adjustment of those limits when operating at site under other conditions and on other ratings. Further rules give adjustments to the limits during thermal testing when conditions at the test site differ from those at the operating site.		P
	The limits are stated relative to the reference coolant specified in Table 4.		P
	A rule is given to allow for the purity of hydrogen coolant.		N
8.10.1	Indirect cooled windings		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	Temperature rises under reference conditions shall not exceed the limits given in Table 7 (air coolant) or Table 8 (hydrogen coolant) as appropriate.		P
	For other operating site conditions, for ratings other than continuous running duty, and for rated voltages greater than 12 000 V, the limits shall be adjusted according to Table 9. (See also Table 10 for limit on coolant temperature which is assumed in Table 9.)		N
	In the case of thermometer readings made in accordance with 8.6.1, the limit of temperature rise shall be according to Table 7.		P
	If, for windings indirectly cooled by air, conditions at the test site differ from those at the operating site, the adjusted limits given in Table 11 shall apply at the test site.		P
	If the adjusted limits given in Table 11 lead to permissible temperatures at the test site which the manufacturer considers to be excessive, the testing procedure and the limits shall be agreed.		N
	No adjustments at the test site are given for windings indirectly cooled by hydrogen, because it is very unlikely that they will be tested at rated load anywhere other than at the operating site.		N
8.10.2	Direct cooled windings		N
	Temperatures under reference conditions shall not exceed the limits given in Table 12.		N
	For other operating site conditions the limits shall be adjusted according to Table 13.		N
	If conditions at the test site differ from those at the operating site, the adjusted limits given in Table 14 shall apply at the test site.		N
	If the adjusted limits given in Table 14 lead to temperatures at the test site which the manufacturer considers to be excessive, the testing procedure and the limits shall be agreed.		N
8.10.3	Adjustments to take account of hydrogen purity on test		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	For windings directly or indirectly cooled by hydrogen, no adjustment shall be made to limits of temperature rise or of total temperature if the proportion of hydrogen in the coolant is between 95 % and 100 %.		N
8.10.4	Permanently short-circuited windings, magnetic cores and all structural components (other than bearings) whether or not in contact with insulation		N
	The temperature rise or the temperature shall not be detrimental to the insulation of that part or to any other part adjacent to it.		N
	Commutators and sliprings, open or enclosed and their brushes and brushgear		N
	The temperature rise or temperature of any commutator, slipring, brush or brushgear shall not be detrimental to the insulation of that part or any adjacent part		N
	The temperature rise or temperature of a commutator or slipring shall not exceed that at which the combination of brush grade and commutator or slipring material can handle the current over the full operating range.		N
9	Other performance and tests		P
9.1	Routine tests		P
	Routine tests are always factory tests. They can only be performed on machines which are assembled at the works of the manufacturer. The machine need not be completely assembled. It can lack components which are not significant for the testing. Routine tests do not need the machine to be coupled except for the open-circuit test on synchronous machines.		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	The minimum test schedule is listed in Table 15 and is applicable for machines with rated output \leq 20 MW (MVA). Additional routine tests may be performed especially on machines with ratings above 200 kW (kVA). The term synchronous machines includes permanent magnet machines.		P
9.2	Withstand voltage test		P
	A test voltage, as specified below, shall be applied between the windings under test and the frame of the machine, with the core and the windings not under test connected to the frame. It shall be applied only to a new and completed machine with all its parts in place under conditions equivalent to normal working conditions and shall be carried out at the manufacturer's works or after erection on site. When a thermal test is carried out, the withstand voltage test shall be carried out immediately after that test.	See append table	P
	In the case of polyphase machines with rated voltage above 1 kV having both ends of each phase individually accessible, the test voltage shall be applied between each phase and the frame, with the core and the other phases and windings not under test connected to the frame		N
	Except as stated below, the test voltage shall be of power frequency and as near as possible to a sine wave form. The final value of the voltage shall be in accordance with Table 16. However, for machines with a rated voltage 6 kV or greater, when power frequency equipment is not available, then by agreement a d.c. test may be carried out at a voltage 1,7 times the r.m.s. value given in Table 16.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	The test shall be commenced at a voltage not exceeding half of the full test voltage. The voltage shall then be increased to the full value, steadily or in steps of not more than 5 % of the full value, the time allowed for the voltage increase from half to full value being not less than 10 s. The full test voltage shall then be maintained for 1 min in accordance with the value as specified in Table 16. There shall be no failure (see IEC 60060-1) during this period.		N
	During the routine testing of quantity produced machines up to 200 kW (or kVA) and rated for UN \leq 1 kV, the 1 min test may be replaced by a test of 1 s at 120 % of the test voltage specified in Table 16.		N
	The withstand voltage test at full voltage made on the windings on acceptance shall not be repeated. If, however, a second test is made at the request of the purchaser, after further drying if considered necessary, the test voltage shall be 80 % of the voltage specified in Table 16.		P
	To determine the test voltage from Table 16 for d.c. motors supplied by static power converters, the direct voltage of the motor or the r.m.s. phase-to-phase value of the rated alternating voltage at the input terminals of the static power converter shall be used, whichever is the greater.		N
	Completely rewound windings shall be tested at the full test voltage for new machines		N
	When a user and a repair contractor have agreed to carry out withstand voltage tests in cases where windings have been partially rewound or in the case of an overhauled machine, the following procedure is recommended:		N
9.3	Occasional excess current		P
9.3.1	General		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	The excess current capability of rotating machines is given for the purpose of co-ordinating these machines with control and protective devices. Tests to demonstrate these capabilities are not a requirement of this standard. The heating effect in the machine windings varies approximately as the product of the time and the square of the current. A current in excess of the rated current will result in increased temperature. Unless otherwise agreed, it can be assumed that the machine will not be operated at the excess currents specified for more than a few short periods during the lifetime of the machine. When an a.c. machine is to be used as both a generator and a motor, the excess current capability should be the subject of agreement.		P
9.3.2	Generators		N
	AC generators having rated outputs not exceeding 1 200 MVA shall be capable of withstanding a current equal to 1,5 times the rated current for not less than 30 s.		N
	AC generators having rated outputs above 1 200 MVA shall be capable of withstanding a current equal to 1,5 times the rated current for a period which shall be agreed, but this period shall be not less than 15 s.		N
9.3.3	Motors (except commutator motors and permanent magnet motors)		P
	Polyphase motors having rated outputs not exceeding 315 kW and rated voltages not exceeding 1 kV shall be capable of withstanding		N
9.3.4	Commutator machines		N
	A commutator machine shall be capable of withstanding, for 60 s, 1,5 times rated current under the appropriate combination of conditions as follows:		N
9.4	Momentary excess torque for motors		P
9.4.1	Polyphase induction motors and d.c. motors		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	Motors, whatever their duty and construction, shall be capable of withstanding an excess torque of at least 60 % of their rated torque for 15 s without either stalling or exhibiting an abrupt change of speed (under gradual increase of torque). The voltage and frequency (for induction motors) shall be maintained at their rated values.		P
	For d.c. motors, the torque shall be expressed in terms of overload current.		N
	Motors for duty type S9 shall be capable of withstanding momentarily an excess torque determined according to the duty specified.		N
	Motors intended for specific applications that require a high torque (for example for hoisting) shall be the subject of agreement.		N
	For cage-type induction motors specially designed to ensure a starting current of less than 4,5 times the rated current, the excess torque can be below the value of 60 % given in paragraph 1, but not less than 50 %.		N
	In the case of special types of induction motors with special inherent starting properties, for example motors intended for use at variable frequency or induction motors supplied from static converters, the value of the excess torque shall be the subject of agreement.		N
9.4.2	Polyphase synchronous motors		N
	Unless otherwise agreed, a polyphase synchronous motor, irrespective of the duty, shall be capable of withstanding an excess torque as specified below for 15 s without falling out of synchronism, the excitation being maintained at the value corresponding to rated load. When automatic excitation is used, the limits of torque shall be the same values with the excitation equipment operating under normal conditions:		N
9.4.3	Other motors		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	The momentary excess torque for single-phase, commutator and other motors shall be the subject of agreement.		N
9.5	Pull-up torque		P
9.6	Safe operating speed of cage induction motors		P
	All three-phase single-speed cage induction motors of frame number up to and including 315 and for voltages up to and including 1 000 V shall be capable of safe continuous operation at speeds up to the appropriate speed given in Table 17 unless otherwise stated on the rating plate.		N
9.7	Overspeed		P
	Machines shall be designed to withstand the speeds specified in Table 18.		P
	An overspeed test is not normally considered necessary but can be performed when this is specified and has been agreed. (For turbine-type a.c. generators, see also IEC 60034-3.) An overspeed test shall be considered as satisfactory if no permanent abnormal deformation is apparent subsequently, and no other weakness is detected which would prevent the machine from operating normally, and provided the rotor windings after the test comply with the required dielectric tests. The duration of any overspeed test shall be 2 min.		P
	Due to settling of laminated rotor rims, laminated poles held by wedges or by bolts, etc. a minute permanent increase in the diameter is natural, and not to be considered as an abnormal deformation indicating that the machine is not suitable for normal operation		N
	During commissioning of a hydraulic-turbine driven synchronous generator, the machine shall be driven at the speed it can reach with the overspeed protection operating, so as to ascertain that the balance is satisfactory up to that speed.		N
9.8	Short-circuit current for synchronous machines		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	Unless otherwise specified, the peak value of the short-circuit current for synchronous machines, including turbine-type machines not covered by IEC 60034-3, in the case of short circuit on all phases during operation at rated voltage, shall not exceed 15 times the peak value or 21 times the r.m.s. value of the rated current.		N
	Verification may be carried out by calculation or by means of a test at a voltage of 0,5 times the rated voltage or above.		P
9.9	Short-circuit withstand test for synchronous machines		N
	The three-phase short-circuit test for synchronous machines shall be carried out only at the request of the purchaser. In this case, the test shall be carried out on the machine running on no-load with an excitation corresponding to the rated voltage unless otherwise agreed. The test shall not be carried out with an excitation greater than that corresponding to 1,05 times the rated voltage at no load.		N
	The test excitation, as determined, may be reduced by agreement, in order to take into account the impedance of the transformer which may be placed between the machines and the system. In this latter case, it may also be agreed that the test be made at the operating site with the over-excitation device in operation. The short circuit shall be maintained for 3 s.		N
	The test is considered satisfactory if no harmful deformation occurs and if the requirements of the applied voltage dielectric test (see Table 16) are met after the short-circuit test. For threephase turbine-type machines, see IEC 60034-3.		N
9.10	Commutation test for commutator machines		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict

	A d.c. or a.c. commutator machine shall be capable of operating from no-load to operation with the excess current or excess torque, specified in 9.3 and 9.4 respectively, without permanent damage to the surface of the commutator or brushes and without injurious sparking, the brushes remaining in the same set position. If possible, the commutation test shall be performed in warm conditions.		N
9.11	Total Harmonic Distortion (THD) for synchronous machines		N
9.11.1	General		N
	The requirements of this subclause apply only to synchronous machines having rated outputs of 300 kW (or kVA) or more, intended for connection to power networks operating at nominal frequencies of 16 2/3 Hz to 100 Hz inclusive, with a view to minimizing interference caused by the machines.		N
9.11.2	Limits		N
	When tested on open-circuit and at rated speed and voltage, the total harmonic distortion (THD) of the line-to-line terminal voltage, as measured according to the methods laid down in 9.11.3, shall not exceed 5 %.		N
9.11.3	Tests		N
	Type tests shall be carried out on a.c. machines to verify compliance with 9.11.2. The range of frequencies measured shall cover all harmonics from rated frequency up to the 100th harmonic.		N
	Either the THD may be measured directly by means of a meter and associated network specially designed for the purpose, or each individual harmonic shall be measured and from the measured values the THD shall be computed using the following formula:		N

10	Rating plates		P
10.1	General		P



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	Electrical machine shall be provided with a rating plate(s). The plates shall be made of durable material and securely mounted.		P
	The rating plate(s) shall preferably be mounted on the frame of the machine and be located so as to be easily legible in the position of use determined by the type of construction and mounting arrangement of the machine. If the electrical machine is so enclosed or incorporated in the equipment that its rating plate is not easily legible, the manufacturer shall, on request, supply a second plate to be mounted on the equipment.		P
10.2	Marking		P
	Machines with rated outputs up to and including 750 W (or VA) and dimensions not covered by IEC 60072 shall be marked with the information given in items 1, 2, 11, 12 and 26 below as a minimum. For special-purpose and built-in machines with rated outputs up to and including 3 kW (or kVA) items 1, 2, 11 and 12 shall be marked a minimum and item 26 may be provided in another form.		P
	In all other cases, rating plate(s) shall be durably marked with the items in the following list,. The items need not all be on the same plate. Letter symbols for units and quantities shall be in accordance with IEC 60027-1 and IEC 60027-4.		P
	If the manufacturer gives more information, this need not necessarily be marked on the rating plate(s).		P
	The items are numbered for convenient reference, but the order in which they appear on the rating plate(s) is not standardized. Items may be suitably combined.		P
11	Miscellaneous requirements		N
11.1	Protective earthing of machines		N
	Machines shall be provided with an earthing terminal or another device to permit the connection of a protective conductor or an earthing conductor.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	The symbol or legend shall identify this device. However, machines shall neither be earthed nor be provided with an earthing terminal when:		N
	In the case of machines having rated voltages greater than 50 V a.c. or 120 V d.c., but not exceeding 1 000 V a.c. or 1 500 V d.c., the terminal for the earthing conductor shall be situated in the vicinity of the terminals for the line conductors, being placed in the terminal box, if one is provided. Machines having rated outputs in excess of 100 kW (or kVA) shall have in addition an earthing terminal fitted on the frame.		N
	Machines for rated voltages greater than 1 000 V a.c. or 1 500 V d.c. shall have an earthing terminal on the frame, for example an iron strap, and in addition, a means inside the terminal box for connecting a conducting cable sheath, if any.		N
	The earthing terminal shall be designed to ensure a good connection with the earthing conductor without any damage to the conductor or terminal. Accessible conducting parts which are not part of the operating circuit shall have good electrical contact with each other and with the earthing terminal. When all bearings and the rotor winding of a machine are insulated, the shaft shall be electrically connected to the earthing terminal, unless the manufacturer and the purchaser agree to alternative means of protection.		N
	When an earthing terminal is provided in the terminal box, it shall be assumed that the earthing conductor is made of the same metal as the live conductors.		N
	When an earthing terminal is provided on the frame, the earthing conductor may, by agreement, be made of another metal (for example, steel). In this case, in designing the terminal, proper consideration shall be given to the conductivity of the conductor.		N



EN 60034-1			
Clause	Requirement-Test	Result	Verdict
	The earthing terminal shall be designed to accommodate an earthing conductor of cross-sectional area in accordance with Table 19. If an earthing conductor larger than the size given in the Table is used, it is recommended that it should correspond as nearly as possible to one of the other sizes listed.		N
	For other cross-sectional areas of live conductors, the earthing or protective conductor shall have a cross-sectional area at least equivalent to:		N
11.2	Shaft-end key(s)		N
	When a machine shaft end is provided with one or more keyways, shall be provided with a full key of normal shape and length.		N
	When a machine shaft end is provided with one or more keyways, shall be provided with a full key of normal shape and length.		N
12	Tolerances		P
12.1	General		P
	Unless stated otherwise, tolerances on declared values shall be as specified in Table 20.		P
13	Electromagnetic compatibility (EMC)	Refer to EMC relevant report	N
13.1	General		N
	The following requirements apply to rotating electrical machines with rated voltages not exceeding 1 000 V a.c. or 1 500 V d.c. and which are intended for operation in industrial environments.		N



	Electronic components mounted inside a rotating electrical machine and which are essential for its operation (for example rotating excitation devices) are part of the machine.		N
	Electronic components mounted inside a rotating electrical machine and which are essential for its operation (for example rotating excitation devices) are part of the machine.		N
	The requirements of this clause apply to machines that are supplied directly to the end-user.		N
	Transients (such as starting) are not covered by this clause.		N
13.2	Immunity		N
13.2.1	Machines not incorporating electronic circuits		N
	Machines without electronic circuits are not sensitive to electromagnetic emissions under normal service conditions and, therefore, no immunity tests are required.		N
13.2.2	Machines incorporating electronic circuits		N
	As electronic circuits which are in machines generally utilize components that are passive (for example diodes, resistors, varistors, capacitors, surge suppressors, inductors), immunity tests are not required.		N
13.3	Emission		N
13.3.1	Machines without brushes		N
	Radiated and conducted emissions shall comply with the requirements of CISPR 11, Class B, Group 1, see Table B.1.		N
13.3.2	Machines with brushes		N
	Radiated and conducted (if applicable) emissions shall comply with the requirements of CISPR 11, Class A, Group 1, see Table B.2.		N
13.4	Immunity tests		N
	Immunity tests are not required.		N
13.5	Emission tests		N
	Type tests shall be carried out in accordance with CISPR 11, CISPR 14 and CISPR 16 as applicable.		N
13.5.1	Machines without brushes		N
	Machines without brushes shall comply with the emission limits of 13.3.1.		N



13.5.2	Machines with brushes		N
	Machines with brushes, when tested at no-load, shall comply with the emission limits of 13.3.2.		N


TABLE: list of critical components				
Object/part No.	Manufacturer/ trademark	Type/model	Technical data	Mark(s) of conformity1)
Slot insulator	Various	PA66	V-0, 130°C	UL
Magnet wire	Various	QAN(AL)-x/130	Class B, 130°C	UL



1) An asterisk indicates a mark which assures the agreed level of surveillance


8.6.2	Determination by resistance method				P
	test voltage (V):	AC 230V		-	
	t1 (°C):	24.1°C		-	
	t2 (°C):	24.4°C		-	
Test condition: output at maximum load for each model.					
Temperature rise dT of winding:	R1(Ω) 1.04	R2(Ω) 1.32	dT (K) 68.4	Required dT (K) 80	Insulation class B
Comments: Base on 40°C					

9.2	TABLE: withstand voltage test		P
Test voltage applied between:		Test voltage (V)	Breakdown
Input and core		AC 500V	No

Photographs of the EUT







(EBO authenticate the photo on original report only)